






TEKNISKE DATA	Egenskaper	Norm	Enhet	BS Strong <sup>TXL</sup>
<p><b>BS Strong</b> </p> <p><b>BS Artigo Strong</b>  Gummi gulvbelegg med runde knaster. Leveres i flis.</p>   <p><b>POLYFLOR</b><sup>TM</sup> COVERING THE WORLD</p> <p><b>Polyflor Nordic</b> Kjelsåsveien 168 B 0884 OSLO Tel.: 23 00 84 00 Fax: 23 00 84 10 <a href="mailto:firmapost@polyflor.no">firmapost@polyflor.no</a> <a href="http://www.polyflor.no">www.polyflor.no</a></p>	Type	EN 12199		
	Overflate			
	Mønster			Ensfarget
	Farger			10
	Totalvekt	EN 430	g/m <sup>2</sup>	5.200
	Klassifisering	EN 685		23, 34, 43
	Totaltykkelse	EN 428	mm	4,0
	Format rull	EN 426	m / m <sup>2</sup>	-
	Format fliser	EN 427	cm	100 x 100
	Restinntrykk	EN 433	mm	0,12
	Slitasjetest	ISO 4649 Met.A-5N	mm <sup>3</sup>	140
	Dimensjonsstabilitet	EN 434	%	± 0,30
	Brann	EN 13501-1		B <sub>fl-s1</sub>
	Friksjon	DIN 13893		DS
	Trinnlydsforbedring	ISO 140-8	dB	10
	Hardhet	ISO 7619 ≥ 75 shore A		90 ± 5
	Elektrisk oppladning	EN 1815	kV	
	El. Motstand	IEC 60093	Ohm	>10 <sup>10</sup>
	Kjemikaliebestandighet	EN 423		ja*
	Rullestol	EN 425		Ja for W hjul
Varmekabler			ja, ikke over 27°C	
*Motstandsdyktig. Ved lengre tids påvirkning eventuelt høy konsentrasjon, vennligst ta kontakt				