

TEKNISKE DATA	Egenskaper	Norm	Enhet	Lava
 <p><b>Lava</b></p> <p><b>Artigo Lava</b> Gummi gulvbelegg. Preget overflate.</p> <p>Leveres i rull og flis.</p>      <p><b>POLYFLOR™</b> COVERING THE WORLD</p> <p><b>Polyflor Nordic</b> Kjelsåsveien 168 B 0884 OSLO Tel.: 23 00 84 00 Fax: 23 00 84 10 <a href="mailto:firmapost@polyflor.no">firmapost@polyflor.no</a> <a href="http://www.polyflor.no">www.polyflor.no</a></p>	Type	EN 1817		
	Overflate			
	Mønster			Sten
	Farger			6
	Totalvekt	EN 430	g/m <sup>2</sup>	4.700
	Klassifisering	EN 685		23, 34, 43
	Totaltykkelse	EN 428	mm	3,0
	Format rull	EN 426	m / m <sup>2</sup>	1,9 x 10 / 19 m <sup>2</sup>
	Format fliser	EN 427	mm / m <sup>2</sup>	61 x 61cm / 5,95 m <sup>2</sup>
	Restintrykk	EN/ISO 24343-1 (EN 433)	mm	0,09
	Slitasjetest	ISO 4649 Met.A-5N	mm <sup>3</sup>	150
	Dimensjonsstabilitet	EN/ISO 23999 (EN 434)	%	± 0,30
	Brann	EN 13501-1		B <sub>fl</sub> -sl
	Friksjon	DIN 51130		R10
	Trinnlyd	ISO 10140-3	dB	Opp til 10
	Hardhet	ISO 7619 shore A		90
	Elektrisk oppladning	EN 1815	kV	≤ 2 (antistatisk)
	El. Motstand	EN 1081 Met.A	Ohm	>10 <sup>10</sup>
	Kjemikaliebestandighet	EN 423		ja*
Trinsestol	EN 425		Ja (W-hjul)	
Varmekabler			ja, ikke over 27°C	
<p>*Motstandsdyktig. Ved lengre tids påvirkning eventuelt høy konsentrasjon, vennligst ta kontakt</p>				