

TEKNISKE DATA

Egenskaper

Norm

Enhet

Camaro Loc PU




LVT med klikksystem.
Moderne, men samtidig klassisk.
Kan legges i alle «tørre» rom.



100% RESIRKULERBAR
40% RESIRKULERT MATERIALE



Except for recycled content



Polyflor Nordic

Kjelsåsveien 168 B
0884 OSLO
Tel.: 23 00 84 00
Fax: 23 00 84 10
firmapost@polyflor.no
www.polyflor.no

Type	EN 649		Heterogen PVC
Overflate			PU
Mønster			Tre / stein
Farger			15
Totalvekt	EN 430	g/m ²	7.025
Klassifisering	EN 685		23, 31
Totaltykkelse	EN 428 EN ISO 24346	mm	4,0
Slitesjikt	EN 429 EN ISO 24340	mm	0,3
Format	EN 427	mm	15 @ 145,6x907,6 = 1,98 m ² 9 @ 177,4x1212,4 = 1,94 m ² 11 @ 298,0 x 602,8 = 1,98 m ²
Format rull	EN 426	m	-
Restinntrykk	EN 433 EN ISO 24343-1	mm	≤ 0,05 ≤ 0,05
Lysekthet	ISO 105-B02 metode A		≥ 6
Brann	EN 13501-1		B _{fl} – S1
Friksjon	DIN 51130 EN 13893		R10 Class DS
Dimensjonsstabilitet	EN434 EN ISO 23999		≤ 0,1 % max ≤ 0,1 % max
Trinsestolfast	EN 425 ISO 4918		Ja
Elektrisk oppladning	EN 1815	kV	< 2 (antistatisk)
El. motstand		Ohm	
Kjemikaliebestandighet	EN 423		*
Slitasjegruppe	EN 649 EN ISO 10582		T Type 1
Varmekabler			ja, ikke over 27°C

* Motstandsdyktig. Ved lengre tids påvirkning eventuelt høy konsentrasjon, vennligst ta kontakt