





TEKNISKE DATA	Egenskaper	Norm	Enhet	Granito Elastic ^{TXL}
<p>Granito Elastic </p> <p>Artigo Granito Elastic</p> <p>Trinnlydsdempende gummi gulvbelegg med filtgranulat bakside. Preget overflate</p> <p>Leveres i rull.</p>   <p>POLYFLORTM COVERING THE WORLD</p> <p>Polyflor Nordic Kjelsåsveien 168 B 0884 OSLO Tel.: 23 00 84 00 Fax: 23 00 84 10 firmapost@polyflor.no www.polyflor.no</p>	Type	EN 1816		
	Overflate			
	Mønster			Chips
	Farger			1
	Totalvekt	EN 430	g/m ²	4.400
	Klassifisering	EN 685		23, 33
	Totaltykkelse	EN 428	mm	4,15
	Format rull	EN 426	m / m ²	1,9 x 10 / 19 m ²
	Format fliser	EN 427	mm / m ²	-
	Restintrykk	EN 433	mm	0,20
	Slitasjetest	ISO 4649 Met.A-5N	mm ³	170
	Dimensjonsstabilitet	EN 434	%	± 0,30
	Brann	EN 13501-1		B _{fl} -sl (bonded)
	Friksjon	EN 13893		DS
	Trinnlyd	ISO 140 - 8	dB	Opptil 20
	Hardhet	ISO 7619 ≥ 75 shore A		85
	Elektrisk oppladning	EN 1815	kV	≤ 2 (antistatisk)
	El. Motstand	IEC 60093	Ohm	>10 ¹⁰
	Kjemikaliebestandighet	EN 423		ja*
	Rullestol	EN 425		Ja (W hjul)
Varmekabler			ja, ikke over 27°C	
<p>*Motstandsdyktig. Ved lengre tids påvirkning eventuelt høy konsentrasjon, vennligst ta kontakt</p>				